


Product code: 33-0441-VP-SUJ-HPD-v1


Revision 1.1

Customer name and address	PerfuseCell standard 4 liter VV B-SUB
Date of contact	
Number of SUB's	
Time of delivery, week from order	
Configurator Version	
Order number	



Dokumentnummer:	Emne:				
K08.2.3.1.3	Production ordre formular – OD 150 mm Vessel				
Version:	Designer:	Document responsible:	Certified by:	Certified (date):	Page:
2	SH	ME	PS	2026-07-08	1

Top plate layout



Dokumentnummer:	Emne:				
K08.2.3.1.3	Production ordre formular – OD 150 mm Vessel				
Version:	Designer:	Document responsible:	Certified by:	Certified (date):	Page:
2	SH	ME	PS	2026-07-08	2

Basic vessel size

Diameter	OD 150 mm (outer diameter)
Model	For sensor length 225 mm
Vessel Volume	4.0 liters

Port description

Port No.	Name	Description	Internal	External
1	Headspace feed line	ID 3 mm barb	N/A.	OD6.4 x ID3.2 x 900 mm weldable hose closed with plug. (PIP230)
2	Sample line	ID 3 mm barb	OD6 x ID3 mm silicone hose set at 70 mm from the bottom.	OD6 x ID3 x 300 mm silicone hose, clamp with swabable valve.
3	Headspace addition line	ID 3 mm barb	N/A.	OD6.4 x ID3.2 x 900 mm weldable hose closed with plug. (PIP230)
4	Prelevement	ID 3 mm barb	OD6 x ID3 mm silicone hose set at 50 mm from the bottom.	OD6.4 x ID3.2 x 900 mm weldable hose with a female Luer-lock (FTLL230) and swabable valve.
5	Headspace feed line	ID 3 mm barb	N/A.	OD6.4 x ID3.2 x 900 mm weldable hose closed with plug. (PIP230)
6	Headspace feed line	ID 3 mm barb	N/A.	OD6.4 x ID3.2 x 900 mm weldable hose closed with plug. (PIP230)
7	Headspace feed line	ID 3 mm barb	N/A.	OD6.4 x ID3.2 x 900 mm weldable hose closed with plug. (PIP230)
8	Headspace addition line	ID 3 mm barb	N/A.	OD6.4 x ID3.2 x 900 mm weldable hose closed with plug. (PIP230)
9	Headspace addition line	ID 3 mm barb	N/A.	OD6.4 x ID3.2 x 900 mm weldable hose closed with plug. (PIP230)
10	Headspace addition line	ID 3 mm barb	N/A.	OD6.4 x ID3.2 x 900 mm weldable hose closed with plug. (PIP230)

Dokumentnummer:	Emne:				
K08.2.3.1.3	Production ordre formular – OD 150 mm Vessel				
Version:	Designer:	Document responsible:	Certified by:	Certified (date):	Page:
2	SH	ME	PS	2026-07-08	3

Product code: 33-0441-VP-SUJ-HPD-v1

Revision 1.1



Port No.	Name	Description	Internal	External
11	Headspace addition line	ID 3 mm barb	N/A.	OD6.4 x ID3.2 x 900 mm weldable hose closed with plug. (PIP230)
12	Headspace Acid/Base line	ID 3 mm barb	N/A.	OD6.4 x ID3.2 x 900 mm weldable hose closed with plug. (PIP230)
13	Center port	PG13.5 port	Shaft for impeller.	HPD bearing.
14	Sky support barb	N/A.	N/A.	N/A.
15	Aeration 1 - Micro	ID7	OD10 x ID7 mm PC tube Micro L-sparger with 16-40µm pore glass frit.	OD12 x ID8 x 100 mm silicone hose with sterile filter OD50. (16cm ²)
16	Temp Well	ID7 mm	OD10 x ID7 mm PC tube.	OD12 x ID8 silicone hose to ensure sealing.
17	Headspace gas overlay	ID4 mm	N/A.	OD11.1 x ID6.4 x 100 mm weldable hose, clamp, with sterile filter OD50. (16cm ²)
18	Aeration 2 - Micro	ID9 mm	Micro L-sparger with 10-16 µm pore glass frit	OD15 x ID10 x 100 mm silicone hose with sterile filter OD50. (16cm ²)
19	Exhaust	PG13.5 port	N/A.	OD15.9 x ID9.6 x 200 mm weldable hose, sterile capsule filter. (400 cm ²)
20	VisiWell	PG13.5 port	Built-in VisiWell sleeve solution for VisiFerm sensor model 225.	Built-in sleeve solution for own Hamilton VisiFerm DO sensor.
21	Harvest	PG13.5 port	OD10 x ID7 mm PC tube with an OD12 x ID8 x 40 mm silicone hose to the bottom with a "V"-cut.	OD9.5 x ID6.4 x 900 mm weldable hose closed with plug. (PIP230)
22	Perfusion	PG21 port	Custom port for insert of CellRetention-PG21-A kit / pn--33-80C112-A	OD19 mm plug + O-ring.
23	Extra PG13.5	PG13.5 port	N/A.	PG13.5 plug + O-ring.
24	OneFerm pH	PG13.5 port	pH sensor model 225	Hamilton OneFerm pH sensor, VP connection, and inbuilt temperature PT100 sensor.
25	Ground port for SS rod	ID 2.5	N/A. (not installed)	For banana-plug.

Dokumentnummer:	Emne:				
K08.2.3.1.3	Production ordre formular – OD 150 mm Vessel				
Version:	Designer:	Document responsible:	Certified by:	Certified (date):	Page:
2	SH	ME	PS	2026-07-08	4

Product code: 33-0441-VP-SUJ-HPD-v1

Revision 1.1

Impeller

Number impeller (from the bottom)	Type of impeller	Diameter of impeller (mm)	Number of blades	Angle (°)	Distance from bottom/lower impeller (mm)
1	Kidney	60	3	45	55


- Clockwise rotation, down flow, without baffles.

Additional information

Single-Use-Jacket (SUJ)

- Single-Use-Jacket – end-user check connection hose length
- In/outlet with G3/8 female threading - Inlet / outlet arranged opposite of each other on wall.
- Top Inlet placed in front of port #1.
- Placed 20 mm +/- 5 mm from the bottom. (measure on the external bottom)

Perfusion (Port22) for insert of CellRetention-PG21-x kit / pn 33-80C112-A



Designed and manufactured by

PerfuseCell-Cronus-PCS A/S

Noerrelundvej 10

DK-2730 Herlev

Denmark

www.perfusecell.com

Dokumentnummer:	Emne:				
K08.2.3.1.3	Production ordre formular – OD 150 mm Vessel				
Version:	Designer:	Document responsible:	Certified by:	Certified (date):	Page:
2	SH	ME	PS	2026-07-08	5